

YKRC1207 Dissolution Tester



YKRC1207 dissolution test instrument is a high-performance 12-cup 12-bar dissolution test device designed and manufactured strictly in accordance with the provisions of Chinese Pharmacopoeia and American Pharmacopoeia. It has high intelligence, advanced structure, accurate control and good reliability. PC cup board and water bath box integrated design, beautiful appearance, easy to observe the test process from multiple angles. High temperature resistance, corrosion resistance, extended service life.

Technical parameter:

- Device number: 12 cups 12 rods (isothermal refill cups can be added).
- Speed zone: (6+6) 2 working areas, 2 batches of dissolution test can be completed at the same time.
- Applicable method: "Chinese Pharmacopoeia" first method (basket method), second method (paddle method), third method (small cup method), fourth method (paddle dish method), fifth method (rotating cylinder method).



0086 16601757347
inquiry@yukelab.com
www.yukelab.com
0086 021 59570209

- Stirring rate: 25RPM-250RPM.(Mixing speed is optional up to 300RPM)
- Stirring direction: Clockwise, counterclockwise.
- Stirring paddle swing amplitude: $\leq 0.3\text{mm}$
- Stirring rate resolution: 0.01RPM.
- Speed error: $\leq 0.5\%$.
- Swing of the basket: $\leq 0.5\text{mm}$
- Deviation between rotating rod and dissolving cup shaft: $\leq 1\text{mm}$
- Water bath temperature: Room temperature -45°C. (The heating temperature is optional up to 55°C)
- Temperature resolution: 0.01°C.
- Temperature control accuracy of water bath: 0.2°C.
- Temperature control accuracy of dissolving medium: 0.2°C.
- Dosing mode: Simultaneous dosing.
- Lifting system: Bamboo square column lifting.
- Authority management: Three levels, seven users.
- Audit trail: 128 items x366 days.
- Operating noise: $< 60\text{db}$
- Environmental condition: Ambient temperature 5-37 °C, relative humidity $\leq 80\%$.
- Safety performance: In line with national industry standards, with self-test and automatic protection functions.
- Power source: 220V, 50Hz

*** Additional and optional items need to be purchased separately.**



0086 16601757347
inquiry@yukelab.com
www.yukelab.com
0086 021 59570209