

Vertical Pressure Steam Sterilizer YK-35/50/75/100/120/150LD



Use

The vertical pressure steam sterilizers are assembled with heating system, microcomputer controlled system, over heat and over pressure protection system, which are reliable for the sterilizing effects, convenient of operation and energy conservation. They are ideal equipments for clinics, scientific research institutes and other organizations to sterilizer surgical instruments, fabrics, glasses, culture media etc.

Characteristics

- Fully stainless steel structure.
- LED display of working status, touch type key.
- Auto discharge the cool air, and steam discharging automatically after sterilization.
- Automatically shut off with beep reminding after sterilization.
- Easy to operate, safe and reliable.
- With two stainless steel sterilizing baskets.



0086 16601757347
 inquiry@yukelab.com
 www.yukelab.com
 0086 021 59570209

Technical Data

MODEL	YK-35LD	YK-50LD	YK-75LD	YK-100LD	YK-120LD	YK-150LD
Technical Data						
Chamber volume	35L φ318×450mm	50L φ340×550mm	75L φ400×600mm	100L φ440×650mm	120L φ480×660mm	150L φ510×740mm
Working pressure	0.22Mpa					
Working temperature	134℃					
Max. working pressure	0.23Mpa					
Heat average	±1℃					
Timer range	0-99min/0-99hour59min					
Temperature adjust range	105-134℃					
Power	2.5KW/AC220V 50HZ	3KW/AC220V 50HZ	4.5KW/AC220V 50HZ		6KW/AC220V 50HZ	
Overall dimension(mm)	470×450×840	520×500×970	550×530×990	580×560×1060	630×610×1130	660×640×1130
Transport dimension (wooden case) (mm)	570×570×1000	610×610×1130	650×650×1150	680×680×1220	730×730×1280	760×760×1280
G.W/N.W(wooden case)	64Kg/46Kg	75Kg/56Kg	90Kg/67Kg	98Kg/73Kg	126Kg/101Kg	136Kg/111Kg