

YKNDJ T Series Intelligent viscometer

New Visual Intelligent Viscometer



Features:

1. 5 inch screen with rich information: easy to operate
2. Anti-static shell and PC lifter
3. RTD temp probe(optional)
4. ARM chip processor: higher data processing speed
5. New designed durable axle
6. Powerful human-computer interactive interface
7. Auto switch between dynamic viscosity and kinematic
8. Variety of viscosity units
9. Detailed operation guide
10. Continuous viscosity value displayed
11. Sound alarm when beyond measurement range
12. Linear calibration by computers
13. Power supply: 100V-240V, good anti-interference

Optional accessories:

Thermostatic water bath (for viscosity measurement)
 Ultra-low viscosity adapter Standard oil
 Micro printer External circulatory glass beaker

Application:

Printing ink, glue, latex, adhesives (solvent base), polymer solutions, oil, painting and coating, solvents, cosmetics, dairy products, pharmaceuticals, juice etc.

YKNDJ T Series Parameters:

| Model | YKNDJ-5S ^T | YKNDJ-8S ^T |
|--------------------|---------------------------------|---------------------------------|
| Range mPa.s | 1-100,000 | 1-2,000,000 |
| Rotate speed (rpm) | 6, 12, 30, 60 | 0.3, 0.6, 1.5, 3, 6, 12, 30, 60 |
| Spindles | 1#, 2#, 3#, 4# (0# is optional) | |
| Accuracy | ±1.0%(of full range) | |
| Repeatability | 0.5% | |